


ARMSTRONG OPTRA FG

- Suitable for open space & large circulation area requiring specialist acoustical performance
- Made from lightweight soft fiber with fully painted surface and edges.
- Customizable sizes & finishing available by request
- High light reflective finish for brighter space
- Humiguard Plus® (RH95) Performance







ARMSTRONG OPTRA FG



	Panel Options	Board		Tegular 24		Tegular 15		SL2 / K2C2
<u>↓</u>	Edge details	24mm Tee Grid		24mm Tee Grid		15mm Tee Grid		24mm Tee Grid
<u>+</u>	Thickness (mm)	15mm	20mm	15mm	20mm	15mm	20mm	20-25mm
(mm	Dimensions (mm) 600 × 600 1200 × 600	G600W060615 G600W061215	G600W060620 G600W061220	G600W060615TL G600W061215TL	G600W060620TL G600W061220TL	G600W060615ML G600W061215ML	G600W060620ML G600W061220ML	Available upon request Available upon request
	1200 x 1200 System	- G600W121220 24mm exposed grid systems fully demountable		- G600W121220TL 24mm exposed grid systems fully demountable		- G600W121220ML 15mm exposed grid systems fully demountable		Available upon request 24mm exposed grid systems fully demountable
K g \	Weight	$1.88 - 2.38 \text{kg/m}^2$						
	Colour	Global White (Black & RAL Colour available by request)						
	Sound absorption	NRC 0.90 (15mm) / 0.95 (20mm)						
*	Sound attenuation	≤ 26 dB						
***	Fire reaction	CLASS 0/1 based on BS 476 Part 6 & 7						
<u> </u>	Light reflectance	≤ 85%						
	Thermal conductivity	$\lambda = 0.052 - 0.057 \text{W/mk}$						
4,4	Humidity resistance	RH95						
	Cleanability							
9% BN HO 14421	Sustainability	Knauf Armstrong provides the widest range of products that have been third party tested and certified by industry leading Eco-classification						

Contact

For further details, please contact your local representative or email asia.support@knaufarmstrong.com

