



ARMSTRONG ULTIMA

- Specially developed for Grade-A workspace application requiring acoustic flexibility
- Best in class durability with Clean Room performance
- Total Acoustics Performance (NRC+CAC) provides excellent sound attenuation and absorption, improving room to room privacy, quieter space, increase concentration, productivity and efficiency
- High light reflective finish up to 88%
- Humiguard Plus® (RH99) Performance

Panel Options	Board	Tegular 24	Tegular 15/90	K2C2 / SL2
Edge details	 24mm Tee Grid	 24mm Tee Grid	 15mm Tee Grid	 24mm Tee Grid
Thickness (mm)	19mm	19mm	19mm	19mm
Dimensions (mm)	600 x 600	1003	1005	-
	1200 x 600	1002	1004	1006
System	24mm exposed grid systems fully demountable	24mm exposed grid systems fully demountable	15mm exposed grid systems fully demountable	Semi-concealed grid system: 24mm exposed long ends with concealed short end fully demountable
Weight	5.0 kg/m ²			
Colour	Global White			
Sound absorption	NRC 0.70			
Sound attenuation	39 dB			
Fire reaction	CLASS 0/1 based on BS 476 Part 6 & 7			
Light reflectance	≤ 88%			
Thermal conductivity	$\lambda = 0.060 \text{ W/mk}$			
Humidity resistance	RH99			
Clean room	ISO 3 as per ISO 14644-1			
Durability				
Cleanability				
Sustainability	<p>Knauf Armstrong provides the widest range of products that have been third party tested and certified by industry leading Eco-classification</p>			

Contact

For further details, please contact your local representative or email asia.support@knaufarmstrong.com